


# DURACELL® Rechargeable



## Rechargeable 9V



Dimensions shown are IEC standards

Product can be charged on most NiMH or NiCd chargers utilizing standard dV, dV/dt, time and temperature dynamic charge termination methods. Duracell brand NiMH chargers are recommended for best results.

Delivered capacity is dependent on the applied load, operating temperature, and cut-off voltage. Please refer to the charts and discharge data shown for example of the energy/service life that the battery will provide for various local conditions.

This data is subject to change. Performance information is typical. Contact Duracell for latest information.

Confidential for internal use only

## BENEFITS

- Reliable Performance in Everyday Devices!

## TECHNICAL

|                              |   |
|------------------------------|---|
| Type:                        | NiMH 9 Volt 170 mAh   |
| Nominal Voltage              | 8.4V  |
| Nominal Internal Impedance:  | < 2 ohm   |
| Average Weight:              | 42.0 grams (1.5 ounces)   |
| Volume:                      | 22.8 cm <sup>3</sup> (1.4 in <sup>3</sup> )                             |
| Operating Temperature Range: | -20° C to 50° C (-4° F to 122° F)                                       |
| ANSI:                        | 8.4H5   |
| IEC:                         | NA  |
| Product Codes                | Blister x1<br>EU/UK SAP Code: 75052469<br>EU/UK EAN Code: 5000394056008 |

LOW RATE DISCHARGE



HIGH RATE DISCHARGE

